

Maintenance instructions

Maintenance Protect Super en Protect Solution

The Zeno-Protect Clean-Off-Zones are designed for use in entrances of buildings to stop the ingress of dirt and water from the outside. Therefore they become soiled with use. This dirt has to be removed in order to keep the Clean-Off-Zones effective.

Recommend maintenance procedure

Daily

Thoroughly vacuum to remove grit, sand and dust. The pile should be agitated. Vacuum cleaners equipped with powerful suction and a rotating brush are most effective in dealing with this task. A vacuum cleaner is effective on dry soiling. It must be in good working order.

Periodically

Protect Super and Solution will collect grease and other sticky substances. A vacuum cleaner is ineffective. A water extraction machine is required to remove greasy soiling. Heavily soiled areas should be pre-treated before the machine is used. It is also recommended to run the machine with clean water (no detergents) to remove the last residues of soiling and detergents. It is important to remove residues of soiling and detergents, as residues will contribute towards shortening the soiling/cleaning cycle. Dry chemical systems (eg Host) are also useful for treating the soiled areas. The dry powder is worked into the pile, left to absorb the soiling and then vacuumed out.

When machines and chemicals are used the instructions of the manufacturers must be closely followed.

Maintenance Protect Star

Protect Star has an open construction.

The material can be rolled backed and the dirt swept up. Grease and fatty deposits can be removed using a water powerhose, possibly with a neutral detergent. Do NOT use detergents that are hydrocarbon based.